




# Model: Solatube 750 DS-C Closed Ceiling (21 in./530 mm Daylighting System)

Project: \_\_\_\_\_ Location: \_\_\_\_\_ Type: \_\_\_\_\_

Product Specifications Appear in CSI Division 08, Section 08 62 23. For budgeting and quotations use only. Qty: \_\_\_\_\_

Model		Capture Zone				Transfer Zone			Delivery Zone												
S	7	5	0	D	S	-	C	-			-	A	K			-					
1		2	2a	3	3a	4	4a	4b	5	5a	5b	6									



## 1 Model

**750 DS-C SolaMaster®** Solatube 750 DS-C (21 in./530 mm Daylighting System)  
Closed Ceiling

## Capture Zone

### 2 Dome

- DA** Acrylic Dome
- DAI** Acrylic Outer Dome + Acrylic Inner Dome
- DPI** Acrylic Outer Dome + Polycarbonate Inner Dome (Required for High Velocity Hurricane Zones)
- MIL** Acrylic Dual Dome (Required for UFC-ATFP)

### 2a Dome Options (Leave blank if not desired)

- B** Security Bar
- PB** Dome Edge Protection Band\*
- SK** Dome Security Kit\*\*

\*Not for use with Curb Cap Flashing  
\*\*Inner dome required for Dome Security Kit

### 3 Flashings

- |   |  |   |
|---|--|---|
| <b>F4</b> 4-inch Self Mounted        | <b>F8</b> 8-inch Self Mounted   | <b>F11</b> 11-inch Self Mounted  |
| <b>FC</b> Curb Cap (Curb by Others)  | <b>FSM</b> Metal Roof Flashing  |   |

### 3a Flashing Options (Leave blank if not desired)

- |  |                                |
|--|--------------------------------|
| <b>T12*†</b> Roof Flashing Turret Extension 12 in./300 mm  | <b>FI</b> Flashing Insulator   |
| <b>T24*†</b> Roof Flashing Turret Extension 24 in./600 mm  | <b>CI</b> Curb Insulator       |
| <b>T36*†</b> Roof Flashing Turret Extension 36 in./900 mm  | <b>CCI</b> Curb Cap Insulation |
| <b>T48*†</b> Roof Flashing Turret Extension 48 in./1200 mm |                                |

\* Specify additional extension tubes in #4a  
† Comes with Bracket Kit

## Transfer Zone


### 4 Top Tube and Bottom Tube Required

**AK** 16" Top Tube Angle Adapter and 16" Bottom Tube Angle Adapter

#### 4a Extension Tubes Required

Run measured from top of roof deck to bottom of ceiling plane along centerline of tubing (allow for 2" overlap) using 24" lengths. See 4b for optional 48" length.

- |   |   |
|---|---|
| <b>E0</b> No Extension Tube – Max Run = 38"       | <b>E6*</b> Six Extension Tubes – Max Run = 170"                     |
| <b>E1*</b> One Extension Tube – Max Run = 60"     | <b>E7*</b> Seven Extension Tubes – Max Run = 192"                   |
| <b>E2*</b> Two Extension Tubes – Max Run = 82"    | <b>E8*</b> Eight Extension Tubes – Max Run = 214"                   |
| <b>E3*</b> Three Extension Tubes – Max Run = 104" | <b>E9*</b> Nine Extension Tubes – Max Run = 236"                    |
| <b>E4*</b> Four Extension Tubes – Max Run = 126"  | <b>E10*</b> Ten Extension Tubes – Max Run = 258"                    |
| <b>E5*</b> Five Extension Tubes – Max Run = 148"  | <b>EXX*</b> Total Run Length to be Determined by Bidding Contractor |



\*Compatible with dome ring to be used as a top tube or extension tube  
\*\*Total tube run will vary depending on flashing used.

#### 4b Extension Tube Options (Leave blank if not desired)

- |   |  |
|---|--|
| <b>A1</b> One 0-90 Degree Extension Tube (Angle Adapter)  | <b>E</b> Wire Suspension Kit (50 ft.)  |
| <b>A2</b> Two 0-90 Degree Extension Tubes (Angle Adapter) | <b>EL</b> Optional 48" Extension Tube (Substitute one 48" for two 24" above) |

## Delivery Zone

### 5 Diffuser Lens

- L1** OptiView® Diffuser  **L2** Prismatic Diffuser 

Diffuser/Ceiling Assembly includes transition box.

#### 5a Effect Lens\* (Leave blank if not desired)

- LN** Natural Effect Lens

\*Effect Lens is optional; does not come standard.

#### 5b Options (Leave blank if not desired)

- D** Daylight Dimmer™

### 6 Measurement Standard

- M** Metric **I** Imperial

#### Accessories (Order separately)

- SW** Low voltage switch (white) required to operate Solatube Daylight Dimmers. Note: Only one switch is required per ten (10) synchronously controlled dimmers.
- CA** Two Conductor Low Voltage Cable (500 ft.)

#### Example

##### 750 DS-C-DAI-FSM-AK-E3-L1-LN-I

SolaMaster Series® 750 DS-C (21 in./530 mm Daylighting System), Acrylic Outer Dome + Acrylic Inner Dome, Metal Roof Flashing, 16" Top Tube Angle Adapter and 16" Bottom Tube Angle Adapter, Three Extension Tubes, OptiView® Diffuser, Transition Box and Natural Effect Lens. For non-metric installations.